

# Arable Shakaerator - Rigid

Working Width 3.0m (9' 10"), 3.7m (12' 2") and 4.5m (14' 9")



### Machine Features

- » 3.0m, 3.7m and 4.5m Working widths
- » Three-point linkage-mounting
- » Unique vibration action
- » Choice of leg configuration
- » Shear bolt protection
- » Choice of replaceable leg points
- » Choice of rear attachments
- » Deep soil conditioning
- » Relieves soil compaction
- » Improves drainage
- » Increases crop yield

### Markets

- » Agricultural
- » Contractors

### Tractor Requirements

- » 120hp minimum tractor horse power (dependent on model)



» Three point linkage kit



» Soil conditioning

Description		3.0m	3.7m	4.5m
Cutting width (m)	Maximum working width (m)	3.0 (9' 10")	3.7 (12' 2")	4.5 (14' 9")
HP requirement	Minimum hp requirement of tractor	100 / 180	180 / 220	180 / 260
Weight (kg)	Weight of the machine	Roller dependent	Roller dependent	Roller dependent
Attachment	Method of attachment to tractor	3 - point	3 - point	3 - point
Replaceable Euroshin	Replaceable shins to protect the legs	Standard	Standard	Standard
Replaceable Europoint	Choice of standard or wide wing Delta point	Standard	Standard	Standard
Transport width (m)	Maximum external width for transport (m)	3.25	3.95	4.75
Transport height (m)	Maximum external height for transport (m)	1.8	1.8	1.8
Leg options	Number of legs	5, 7, 9	9, 11	9, 11, 13
Leg length (mm)	Length of leg assembly (mm)	600	600	600
Packer roller	600mm packer roller / 600 or 800mm Ridge packer	Optional	Optional	Optional
Three point linkage kit	Kit for attaching by Three point linkage	Optional	Optional	Optional
Grassland disc assembly	Disc assembly for Grassland usage	Optional	Optional	Optional