



FLAIL MOWER

# MAGNUM OPEN

**MAGNUM OPEN 230**

- 2.20m (7'2") working width

**MAGNUM OPEN 250**

- 2.40m (7'8") working width

**MAGNUM OPEN 280**

- 2.70m (8'8") working width

## MAGNUM OPEN SERIES

MODEL	MAGNUM OPEN 230	MAGNUM OPEN 250	MAGNUM OPEN 280
<b>Specification</b>			
Working width	2.20m (7'2")	2.40m (7'8")	2.70m (8'8")
Cutting height	30mm-100mm	30mm-100mm	30mm-100mm
Cutting capacity	75mm	75mm	75mm
<b>Tractor requirement &amp; attachment</b>			
HP requirement	55	65	75
Method of attachment	3-point linkage	3-point linkage	3-point linkage
<b>Dimensions</b>			
Weight	758kg	790kg	843kg
Overall width	2.50m (8'2")	2.70m (8'10")	3.00m (9'10")
<b>Equipment details</b>			
PTO speed	1,000rpm	1,000rpm	1,000rpm
Protection	Slip clutch	Slip clutch	Slip clutch
Number of flails	26	28	32
Hydraulic offset	500mm (1'8")	500mm (1'8")	750mm (2'5")
Roller diameter	168	168	168



# PRECISION AND PERFORMANCE

McConnel's heavy-duty Magnum Open brings all the benefits of the professional-spec Combi model, but adds an adjustable rear gate that allows operators to customise the flow of material through the mower to suit a wide range of applications.

Available in three different working widths from 2.2m to 2.7m, the Open range can be adjusted to deliver everything from a fine-cut finish to a heavy-duty mulch.

## KEY FEATURES

Designed for busy farmers, contractors and local government teams, the Open series delivers power, precision and reliability while still being compatible with tractors of just 55hp and upwards.

- 2.2m, 2.4m, and 2.7m working widths
- Three-point linkage mounting
- Five-position rear gate
- 1,000rpm PTO speed
- 75mm cutting capacity
- 30-100mm cutting height
- Durable design
- Whale-tail flails
- Slip clutch protection
- 500mm - 750mm hydraulic offset
- Adjustable rear roller
- Replaceable full-length steel skids

