

Grassland Shakaerator

Working Width 2.0m (6' 7"), 2.5m (8' 2") and 3.0m (9' 10")



Machine Features

- » 2.0m, 2.5m and 3.0m working widths
- » Three-point linkage-mounting
- » Unique vibration action
- » 2 to 5 leg configuration
- » Spring loaded grassland discs
- » Adjustable wheel roller assembly
- » Unique profile legs
- » Replaceable Euroshin and Longlife points
- » Minimum turf and surface disturbance
- » Deep soil conditioning, relieves soil compaction
- » Increases crop yield
- » Excellent for pastures, arable leys and sports grounds

Markets

- » Horticultural
- » Groundcare
- » Governmental
- » Contractors

Tractor Requirements

- » 50hp minimum tractor horse-power

Gas Strut Break Back Legs

Revolutionary new leg breakaway system featuring fully independent gas-strut pressure release



» Full Width Roller



» Pasture Maintenance

Description		2.0m	2.5m	3.0m
Working width (m)	Maximum working width	2.0 (6' 7")	2.5 (8' 2")	3.0 (9' 10")
HP requirement	Minimum hp requirement of tractor	50	75	100
Attachment	Method of attachment to tractor	3 Point Linkage	3 Point Linkage	3 Point Linkage
Vibration unit	540 rpm vibration unit	Optional	Optional	Optional
Number of legs	Choice of leg configurations	2-3	3-4	4-5
Fixed leg	600mm (24") leg with shearbolt protection	Optional	Optional	Optional
Mechanical Breakback leg	750mm (30") knock through shear pin protection (4 lives)	Optional	Optional	Optional
Hydraulic Breakback leg	750mm (30") hydraulic protection with auto reset	Optional	Optional	Optional
Replaceable Euroshins	Protects leg from wear	Standard	Standard	Standard
Leg points	Longlife leg points	Standard	Standard	Standard
Roller	Full width rear roller with scrapper bar	Standard	Standard	Standard
Grassland disc's	Adjustable, spring loaded disc assemblies	Standard	Standard	Standard