



FLAIL MOWER

MAGNUM COMBI

MAGNUM COMBI 230 - 2.20m (7'2") working width
MAGNUM COMBI 250 - 2.40m (7'8") working width
MAGNUM COMBI 280 - 2.70m (8'8") working width

MAGNUM COMBI SERIES

MODEL	MAGNUM COMBI 230	MAGNUM COMBI 250	MAGNUM COMBI 280
Specification			
Working width	2.20m (7'2")	2.40m (7'8")	2.70m (8'8")
Cutting height	30mm-100mm	30mm-100mm	30mm-100mm
Cutting capacity	75mm	75mm	75mm
Tractor requirement & attachment			
HP requirement	50	70	80
Method of attachment	3-point linkage	3-point linkage	3-point linkage
Dimensions			
Weight	776kg	810kg	864kg
Overall width	2.50m (8'2")	2.70m (8'10")	3.00m (9'10")
Equipment details			
PTO speed	1,000rpm	1,000rpm	1,000rpm
Protection	Slip clutch	Slip clutch	Slip clutch
Number of flails	26	28	32
Hydraulic offset	500mm (1'8")	500mm (1'8")	750mm (2'5")
Roller diameter	168	168	168



PRODUCTIVE AND POWERFUL

Tougher, stronger and more productive than the popular Magnum Elite Series, McConnell's Combi machines offer a choice of 2.2m, 2.4m and 2.7m cutting widths and make light work of material up to 75mm thick.

Designed for tackling grass, gorse, OSR and maize stubble, the Combi series offers a cutting power and versatility that is much sought after by large-scale farmers, contractors, and local government teams.

KEY FEATURES

Created to thrive on busy workloads, the three Combi machines boast rugged build quality, PTO over-run protection, full-length replaceable skids, and automatic belt tensioning.

- 2.2m, 2.4m, and 2.7m working widths
- Three-point linkage mounting
- Front and rear mounting
- 1000rpm PTO speed
- 75mm cutting capacity
- 30-100mm cutting height
- Durable design
- Whale-tail flails
- Slip clutch protection
- 500mm - 750mm offset
- Adjustable rear roller
- Replaceable full-length skids

