



MERLIN



FLAIL MOWER

MERLIN XTREME

MERLIN XTREME 2000 - 2.00m (6'7") working width
MERLIN XTREME 2500 - 2.45m (8'0") working width
MERLIN XTREME 2800 - 2.65m (8'8") working width

MERLIN XTREME SERIES

MODEL	MERLIN XTREME 2000	MERLIN XTREME 2500	MERLIN XTREME 2800
Specification			
Working width	2.00m (6'7")	2.45m (8'0")	2.65m (8'8")
Cutting height	0mm-150mm	0mm-150mm	0mm-150mm
Cutting capacity	50mm	50mm	50mm
Tractor requirement & attachment			
HP requirement	50	60	70
Method of attachment	3-point linkage	3-point linkage	3-point linkage
Dimensions			
Weight	730kg	814kg	860kg
Transport width	2.3m	2.8m	3.0m
Equipment details			
PTO speed	1000rpm	1000rpm	1000rpm
Protection	Slip clutch	Slip clutch	Slip clutch
Number of flails	48	60	66
Roller diameter	166mm	166mm	166mm



PERFORMANCE FLAIL MOWER

A range of tough, productive, heavy-duty flail mowers, the Merlin Xtreme series is designed and precision-engineered in the UK by McConnell and offers a choice of cutting widths from 2.0m to 2.65m.

Robust and reliable, the machines are exceptionally versatile with a hydraulic offset and the option of front or rear mounting. The machines come with a choice of J-flails or back-to-back flails and deliver a fine cut finish.

KEY FEATURES

Created for large-scale farmers, contractors and local government teams, Merlin Xtreme mowers can tackle vegetation up to 50mm thick and offer a wide range of cutting heights from 0-150mm.

- 2.0m, 2.45m, 2.65m working widths
- Three-point linkage mounting
- 1,000rpm PTO speed
- Adaptable for use with a 540rpm PTO
- Robust build quality
- PTO over-run protection
- 50 mm cutting capacity
- 600mm offset
- Belt drive
- Sliding hitch for central or offset mounting

