



FLAIL MOWER

# MAGNUM MEGA

- MAGNUM MEGA 250**  
- 2.40m (7'8") working width
- MAGNUM MEGA 270**  
- 2.60m (8'6") working width
- MAGNUM MEGA 300**  
- 2.90m (9'6") working width



## MAGNUM MEGA SERIES

MODEL	MAGNUM MEGA 250	MAGNUM MEGA 270	MAGNUM MEGA 300
<b>Specification</b>			
Working width	2.40m (7'8")	2.60m (8'6")	2.90m (9' 6")
Cutting height	40mm-150mm	40mm-150mm	40mm-150mm
Cutting capacity	100mm	100mm	100mm
<b>Tractor requirement &amp; attachment</b>			
HP requirement	65	80	95
Method of attachment	3-point linkage	3-point linkage	3-point linkage
<b>Dimensions</b>			
Weight	1120kg	1173kg	1241kg
Overall width	2.73m (8'11")	2.93m (9'7")	3.22m (10'7")
<b>Equipment details</b>			
PTO speed	1,000rpm	1,000rpm	1,00rpm
Protection	Slip clutch	Slip clutch	Slip clutch
Hydraulic Offset	900mm (2'11")	900mm (2'11")	900mm (2'11")
Number of flails	20	22	26
Rear roller diameter	194mm	194mm	194mm



# HEAVY-DUTY MULCHER

Available in 2.4m, 2.6m and 2.9m working widths, the Mega is McConnel's most powerful flail mower. It is capable of cutting through vegetation up to 100mm thick and is ideal for fast, effective mulching in gorse, dense overgrowth and thick stubble.

Featuring heavy-duty build quality throughout, the Mega thrives on heavy workloads and in challenging environments making it an ideal tool for forestry specialists, full-time contractors and local government.

## KEY FEATURES

Flexibility is key with front and rear mounting available and a fully adjustable five-position rear gate, allowing operators to spec the machine to deliver everything from a fine-cut finish to a heavy-duty mulch.

- 2.4m, 2.6m, and 2.9m working widths
- Three-point linkage mounting
- Five-position rear gate
- Double row ball-bearings on the rotor shaft
- 1,000rpm PTO speed
- 100mm cutting capacity
- Durable design
- Slip clutch protection
- 900mm hydraulic offset
- Adjustable rear roller
- Replaceable full-length steel skids

