



MERLIN



FLAIL MOWER

MERLIN XTREME OFFSET

- MERLIN XTREME OFFSET 1200**
- 1.20m (3'11") working width
- MERLIN XTREME OFFSET 1600**
- 1.60m (5'3") working width
- MERLIN XTREME OFFSET 2000**
- 2.00m (6'7") working width

MERLIN XTREME OFFSET SERIES

MODEL	MERLIN XTREME OFFSET 1200	MERLIN XTREME OFFSET 1600	MERLIN XTREME OFFSET 2000
Specification			
Working width	1.20m (3'11")	1.60m (5'3")	2.00m (6'7")
Cutting height	15mm-155mm	15mm-155mm	15mm-155mm
Cutting capacity	50mm	50mm	50mm
Tractor requirement & attachment			
HP requirement	50	60	70
Method of attachment	3-point linkage	3-point linkage	3-point linkage
Dimensions			
Weight	1010kg	1060kg	1150kg
Equipment details			
PTO speed	540/1000rpm	540/1000rpm	540/1000rpm
Protection	Slip clutch	Slip clutch	Slip clutch
Number of flails	38	48	66
Hydraulic adjustment range	90° up, 60° down	90° up, 60° down	90° up, 60° down



PROFESSIONAL OFFSET MOWING

Combining the power and durability of the Merlin range with a heavy-duty offset, these machines deliver exceptional results for busy verge mowing professionals.

A choice of cutting widths from 1.2m to 2.0m is available, as well as advanced features such as hydraulic safety breakaway, 120 degrees of head movement, and front or rear mounting.

KEY FEATURES

Precision-engineered in the UK and created for contractors, local government, and highway maintenance teams, Merlin Xtreme Offset machines can tackle vegetation up to 50mm thick and feature a 150 degree hydraulic floatation system.

- 1.2m, 1.6m, 2.0m working widths
- Three-point linkage mounting
- Front or rear mounting
- 600mm hydraulic offset adjustment
- 540 or 1,000rpm PTO speed
- Hydraulic floatation system (+90° to -60°)
- Robust build quality
- PTO over-run protection
- Hydraulic safety breakaway
- 50mm cutting capacity
- Left or right hand cut options
- Replaceable full-length skids

