



ROTARY MOWER

PT SERIES

PT180 - 1.80m (5'11") working width
PT270 - 2.70m (8'10") working width
PT240 OFFSET - 2.40m (7'11") working width

PT SERIES

MODEL	PT180	PT270	PT240 OFFSET
Specification			
Working width	1.80m (5'11")	2.70m (8'10")	2.40m (7'11")
Cutting height	50mm-175mm	50mm-175mm	50mm-175mm
Cutting capacity	30mm	30mm	30mm
Tractor requirement & attachment			
HP requirement	30	30	30
Method of attachment	3-point linkage (Cat I & II)	3-point linkage (CAT I & II)	3-point linkage (Cat I & II)
Dimensions			
Weight	330kg	470kg	680kg
Overall width (Transport)	1.96m	2.98m	1.85m
Equipment details			
PTO speed	540rpm	540rpm	540rpm
Protection	Shear bolt	Shear bolt	Shear bolt
Blade carriers	1	2	2
Number of rotors	1	2	2
Number of blades	2	4	4
Skids	2	2	2



VERSATILITY AND VALUE

Productivity and value are what define McConnel's range of PT Toppers. With a choice of working widths from 1.8m to 2.7m, an entry-level offset model and PTO overrun protection, the range is ideal for those seeking a productive and reliable topper at a competitive price.

Designed for farmers and small-scale contractors, McConnel's PT Series features three distinct models: A 1.8m model for those seeking a cost-effective pasture mower, a 2.4m offset for verge mowing, and a highly productive 2.7m machine.

KEY FEATURES

Low power requirements (30hp) make the PT series an ideal choice for customers with older or compact tractors. Three diverse machines are available, with a choice of compact, offset and 2.7m models.

- 1.8m, 2.4m, and 2.7m working widths
- Three-point linkage
- 540rpm PTO speed
- Direct drive
- Shearbolt protection
- 50mm-170mm cutting height
- 30mm cutting capacity
- Low tractor horsepower requirements
- Full length replaceable skids

