



ROTARY MOWER
SR460

SR460 - 4.60m (15') working width

SR SERIES

MODEL	SR460
Specification	
Working width	4.60m (15')
Cutting height	25mm-400mm
Cutting capacity	50mm
Tractor requirement & attachment	
HP requirement	70
Method of attachment	Drawbar
Dimensions	
Weight	2200kg
Overall width	4.8m
Overall length	4.85m
Transport width	2.8m
Transport height	1.8m
Equipment details	
PTO speed	1,000rpm
Protection	Slip clutch
Number of blades	6, 9, 12 or 18
Number of rotors	3
Blade overlap	110mm
Blade tip speed	5340m/min
Hydraulic wing flex	90° up, 25° down
Wheels	6 or 8



FAST, FLEXIBLE, FEATURE-PACKED

The bigger sibling of the SR420, the SR460 offers 4.6m cutting width, greater wing flexibility – with a movement range of 115 degrees – and the option of walking axles for a smoother ride over the ground.

Designed for productivity with three high-performance rotors and a choice of six or 18 hardened updraft swinging blades, the SR460 can tackle material up to 50mm thick and delivers an exceptionally clean cut with an even spread of material.

KEY FEATURES

Ideal for large-scale farmers, local government teams, and professional mowing contractors, SR series machines can be used in a huge variety of applications from airports and sports venues to pasture and stubble.

- 4.6m working widths
- High and low hitch options
- Bondioli & Pavesi gearboxes and drivelines
- 115 degrees of wing movement (+90° up, -25° down)
- 1000rpm wide angle PTO
- Slip clutch protection
- Front and rear chain guards
- Cutting heights from 25mm to 400mm
- 50mm cutting capacity
- 6, 9, 12 or 18 blades
- Overlapping blades
- Low tractor hp requirement (70hp)

