



ROTARY MOWER

# SE SERIES

SE5 - 1.50m (5') working width  
SE6 - 1.80m (5'11") working width  
SE7 - 2.10m (6'10") working width



## SE SERIES

MODEL	SE5	SE6	SE7
<b>Specification</b>			
Working width	1.50m (5')	1.80m (5'11")	2.10m (6'10")
Cutting height	25mm-150mm	19mm-150mm	25mm-150mm
Cutting capacity	25mm	25mm	25mm
<b>Tractor requirement &amp; attachment</b>			
HP requirement	20	30	40
Method of attachment	3-point linkage	3-point linkage	3-point linkage
<b>Dimensions</b>			
Weight	300kg	430kg	470kg
Overall width	1.6m	1.9m	2.3m
Overall length	2.5m	2.7m	3.1m
<b>Equipment details</b>			
PTO speed	540	540	540
Protection	Slip Clutch	Slip Clutch	Slip Clutch
Blade carriers	1	1	1
Blade overlap	38	38	38
Blade tip speed	3800m/min	4550m/min	4550m/min
Wheels	1	1	1



# TOUGH AND MANOEUVRABLE

A light, durable, and highly manoeuvrable rotary mower that offers a solid combination of performance and value for farmers.

Available in three different working widths from 1.5m to 2.1m, the SE series is highly flexible and can be used in a wide variety of green maintenance jobs from park maintenance to pasture topping.

## KEY FEATURES

Robust and reliable, SE series machines are equipped with a range of features to boost performance, safety and durability including slip clutch protection, front and rear chain guards, and full-length replaceable skids.

- 1.5m, 1.8m and 2.1m working widths
- Three-point linkage
- Direct drive
- 12-150mm cutting height
- 25mm cutting capacity
- Updraft blades
- Blade tip speeds of up to 4550 metres per minute
- 360-degree swivel wheel
- Puncture-proof tyre
- Slip clutch protection
- Front and rear chain guards
- Full length replaceable skids

